

## 6D Cylinder

# CYLINDER SPECIFICATIONS

**Cylinder**

6D

**Gas Contents at Full Service Pressure**

103 litres

**Service Pressure**

1000 psig/69 bar

**Dimensions**

346mm x 83mm

**Weight**

1.4kg

**Colour**

Beige

**Primary Uses**

LEL mixtures, instrument zero gases (Air and Nitrogen), Oxygen deficiency mixtures, Carbon Monoxide mixtures and Isobutylene mixtures.

**Recommended Equipment**

Model 715, DFR 2000 Series, or Trigger regulators. Connection is 5/8" x 18 UNF thread (not CGA connection).

**Mixture Tolerance**

All minor components are certified to +/-2%.

**Warranty**

All gases are warranted for 36 months.

**Meets European Standards**

The 6D cylinder with patented "One Fill Valve" meets European Standards EN12205 requiring that all non-refillable cylinders be fitted with a one way valve to prevent refilling.

NOT REFILLABLE UNDER EUROPEAN REGULATIONS.



# CALGAZ



RAE BeNeLux BV  
Rijndal 20  
2904 DC Capelle a/d IJssel  
The Netherlands  
tel. +31-(0)10-4426149  
fax +31-(0)10-4426148  
info@RAE.nl